



AMERICA'S AUTOMATIC MOTORCYCLE

## Service & Maintenance Quick Reference Replacement Parts

Part	Part No.	Inspection (I)/Replacement (R)	Year(s)	Note
Type II Transmission Belt	12447	I- 2,000 R-6,000	2003 - up	w/Type II trans. Most Models
Type I Transmission Belt	13676	I- 2,000 R-4,000	2003 - up	w/Type I trans. Incl. Auto-Glide Standard
Clutch Lubricant	12529	Lubricate Drives @ 2,000	2003 - up	
Type II Drive Clutch (New)	11940	I- 2,000 R-10,000	2003 - up	
Type II Drive Clutch (Reman.)	12945	Remanufactured Clutch	2003 - up	
Type II Driven Clutch	11941	I- 2,000 R- 10,000	2003 - up	
Driven Clutch Cam Buttons	12610	I- 2,000 R- As needed	2003 - up	Package of 3.
Oil	13423	Initial- 500 R- 2,000	2003 - up	Mobil One 10W-30
Oil Filter	11801	Initial- 500 R- 2,000	2003 - up	Recommended K&N Chrome Filter. KN-171C
Fuel Filter	12096	Initial- 500 R- 2,000	2003 - up	Recommended Disposable Filter.
Fork Oil	71904	R- 10,000	2003 - up	Recommended 15W Fork Oil
Throttle Cable Lubricate	92528	Lubricate Cables @ 4,000	2003 - up	
Battery	32146	I- 2,000 R- As needed	2003 - up	Interstate Battery FAYTX20HL.
Air Filter Cleaner	91996	Clean filter @ 2,000	2003 - up	K&N Filter Recharge Kit.
White Wall Cleaner	93672	Clean white wall tires as needed.	2003 - up	Excellent White Wall Cleaner



# Service & Maintenance Reference

## 38 Point Inspection

Ridley recommends following the 38 point inspection for:

- Pre-Delivery Inspection to New Owner
- 500 mile post purchase inspection
- Seasonal Condition Inspection
- All newly acquired Pre-Owned Motorcycles

## RIDLEY 38 POINT INSPECTION

Owner: \_\_\_\_\_ VIN: \_\_\_\_\_ Date: \_\_\_\_\_

Inspector: \_\_\_\_\_ Dealer: \_\_\_\_\_ Mileage: \_\_\_\_\_

Please fax copy to Ridley Motorcycle at (405) 525-5438. 500 mile Inspection required for 2 Year Plus Warranty.

<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 5%; text-align: center;">/</td> <td style="width: 45%;">Service</td> <td style="width: 50%;"></td> </tr> <tr> <td></td> <td>Tire Pressure</td> <td>Front (PSI) : Rear (PSI) :</td> </tr> <tr> <td></td> <td>Belt/Chain Inspection</td> <td>Tension Wear</td> </tr> <tr> <td></td> <td>Chain Lubrication</td> <td></td> </tr> <tr> <td></td> <td>Transmission Inspection</td> <td>Clutch: Face / Bell / Guides Driven: Face / Ramps / Cam Buttons</td> </tr> <tr> <td></td> <td>Electrical System</td> <td>Battery Condition: _____ volts Output: _____ amps @ 2000rpm</td> </tr> <tr> <td></td> <td>Handlebar Inspection</td> <td>Dampeners Alignment</td> </tr> <tr> <td></td> <td>Brakes Inspection</td> <td>Pads   Brake Lines Rear Pedal   Calipers</td> </tr> <tr> <td></td> <td>Frame/Body Inspection</td> <td>Condition: Adjustment: Fender Spacing</td> </tr> <tr> <td></td> <td>Throttle Cable Inspection</td> <td>Action: Respring / adjustment Lubrication:</td> </tr> <tr> <td></td> <td>Carburetor Adjustment</td> <td>Idle RPM: Idle Mixture:</td> </tr> </table>	/	Service			Tire Pressure	Front (PSI) : Rear (PSI) :		Belt/Chain Inspection	Tension Wear		Chain Lubrication			Transmission Inspection	Clutch: Face / Bell / Guides Driven: Face / Ramps / Cam Buttons		Electrical System	Battery Condition: _____ volts Output: _____ amps @ 2000rpm		Handlebar Inspection	Dampeners Alignment		Brakes Inspection	Pads   Brake Lines Rear Pedal   Calipers		Frame/Body Inspection	Condition: Adjustment: Fender Spacing		Throttle Cable Inspection	Action: Respring / adjustment Lubrication:		Carburetor Adjustment	Idle RPM: Idle Mixture:	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 5%; text-align: center;">/</td> <td style="width: 45%;">Service</td> <td style="width: 50%;"></td> </tr> <tr> <td></td> <td>Speedometer Inspection</td> <td>Sender: Indicators Speed Reading</td> </tr> <tr> <td></td> <td>Steering Bearing Inspection</td> <td>Spindle Rotation</td> </tr> <tr> <td></td> <td>Mirrors</td> <td>Tighten: Adjustment / Clamp</td> </tr> <tr> <td></td> <td>Wheel Bearing Inspection</td> <td>Front Rear</td> </tr> <tr> <td></td> <td>Lighting Inspection</td> <td>Switches: Right / Left Front-Right: Lens / Board / Function Front-Right: Lens / Board / Function Rear-Right: Lens / Board / Function Rear-Right: Lens / Board / Function</td> </tr> <tr> <td></td> <td>Suspension Inspection</td> <td>Front: Action / Rebound / Seals Rear: Action / Rebound / Adjustment</td> </tr> <tr> <td></td> <td>Kickstand Inspection</td> <td>Spring Bend</td> </tr> <tr> <td></td> <td>Fluids</td> <td>Brake   Oil   Fuel Filter</td> </tr> <tr> <td></td> <td>NOTES:</td> <td></td> </tr> </table>	/	Service			Speedometer Inspection	Sender: Indicators Speed Reading		Steering Bearing Inspection	Spindle Rotation		Mirrors	Tighten: Adjustment / Clamp		Wheel Bearing Inspection	Front Rear		Lighting Inspection	Switches: Right / Left Front-Right: Lens / Board / Function Front-Right: Lens / Board / Function Rear-Right: Lens / Board / Function Rear-Right: Lens / Board / Function		Suspension Inspection	Front: Action / Rebound / Seals Rear: Action / Rebound / Adjustment		Kickstand Inspection	Spring Bend		Fluids	Brake   Oil   Fuel Filter		NOTES:	
/	Service																																																															
	Tire Pressure	Front (PSI) : Rear (PSI) :																																																														
	Belt/Chain Inspection	Tension Wear																																																														
	Chain Lubrication																																																															
	Transmission Inspection	Clutch: Face / Bell / Guides Driven: Face / Ramps / Cam Buttons																																																														
	Electrical System	Battery Condition: _____ volts Output: _____ amps @ 2000rpm																																																														
	Handlebar Inspection	Dampeners Alignment																																																														
	Brakes Inspection	Pads   Brake Lines Rear Pedal   Calipers																																																														
	Frame/Body Inspection	Condition: Adjustment: Fender Spacing																																																														
	Throttle Cable Inspection	Action: Respring / adjustment Lubrication:																																																														
	Carburetor Adjustment	Idle RPM: Idle Mixture:																																																														
/	Service																																																															
	Speedometer Inspection	Sender: Indicators Speed Reading																																																														
	Steering Bearing Inspection	Spindle Rotation																																																														
	Mirrors	Tighten: Adjustment / Clamp																																																														
	Wheel Bearing Inspection	Front Rear																																																														
	Lighting Inspection	Switches: Right / Left Front-Right: Lens / Board / Function Front-Right: Lens / Board / Function Rear-Right: Lens / Board / Function Rear-Right: Lens / Board / Function																																																														
	Suspension Inspection	Front: Action / Rebound / Seals Rear: Action / Rebound / Adjustment																																																														
	Kickstand Inspection	Spring Bend																																																														
	Fluids	Brake   Oil   Fuel Filter																																																														
	NOTES:																																																															



AMERICA'S AUTOMATIC MOTORCYCLE

## Service & Maintenance Reference Manuals

Name	Description	Part No.
Service & Maintenance Guide	Owner & Technicians reference guide for required services on all 2006-up Auto-Glide models. Includes interval chart, servicing instructions with photos, service notes, and plastic carrying case that mounts under the seat of the motorcycle.	93666
Service Manual	Technician's reference manual for all Ridley Auto-Glide models- all years. Includes wiring diagrams, repair, replacement, and inspection instructions, parts list, and Service Notices. Yearly updates can be inserted. <b>---Available August 2008---</b>	TBA
Owners Manual- '03 Auto-Glide	Original Owners Manual for 2003 Auto-Glide Models.	92083-3
Owners Manual- '04 Auto-Glide	Original Owners Manual for 2004 Auto-Glide Models.	92083-4
Owners Manual- '05 Auto-Glide	Original Owners Manual for 2005 Auto-Glide Models.	92083-5
Owners Manual- '06 Auto-Glide	Original Owners Manual for 2006 Auto-Glide Models.	92083-6
Owners Manual- '07 Auto-Glide	Original Owners Manual for 2007 Auto-Glide Models.	92083-7
Owners Manual- '08 Auto-Glide	Original Owners Manual for 2008 Auto-Glide Models.	92083-8





AMERICA'S AUTOMATIC MOTORCYCLE

## Service & Maintenance Reference

### Motor Oil & Filter Change

#### OIL SPECIFICATIONS

Oil Type	Mobil One 10W 30
Oil Volume	1 $\frac{3}{4}$ Quarts
Oil Filter	RMC 11801 (KN-171C)
Oil Level	The Dipstick has two holes. The oil level should be 1/8" below the top hole. Level must be checked with motorcycle in upright position (off side stand) and dipstick screwed completely in. Remove dipstick and read level.

**CAUTION:** Overfilling with oil will cause oil to exit through breather vent into the air filter which leads to excess smoke from exhaust.